```
                          DSL
                       Subscriber

        DSL                                    DSL
     Subscriber                             Subscriber

  DSL                                                      DSL
Subscriber                                             Subscriber

                        Central
                        Office
```

Fig. 1

4 Port Modem

```
        Interface        Framer      Transformation     Equalizer    Line 1
          Block          Block           Block            Block

        Interface        Framer      Transformation     Equalizer    Line 2
          Block          Block           Block            Block

        Interface        Framer      Transformation     Equalizer    Line 3
          Block          Block           Block            Block

        Interface        Framer      Transformation     Equalizer    Line 4
          Block          Block           Block            Block
```

Fig. 2

Fig. 3

100

Line

500

510 — Interpolator Echo Cancellation

520 — Echo Cancellation TDQ

440 — DMT Modulator (IFFT)

450 — DMT Demodulator (FFT/FDQ)

400

410 — QAM Encoder Trellis

420 — QAM Decoder Trellis

430 — Equalizer

2/10

350 — Interleaver

330 — Reed Solomon Coder

360 — Deinterleaver

340 — Reed Solomon Decoder

300

310 — Framer CRC Scrambler

320 — Inv-Framer CRC Descrambler

5

200 — Utpoia II TC Layer

600 — Resource Manager

5

5

Fig. 4

Fig. 5

Resource Manager (Memory and Resource Multiplexing Control)

600

Addressing and Control

660

5

670

330

410

440

Reed-
Solomon
Encode
Engine

Encoder
Output
Buffer

Constellation
Encode
Engine

FFT
Inplace
Buffer

FFT
MACC
Engine

Fig. 6

Fig. 7

```
        ( Begin )        S100

        ┌─────────────┐
        │  Establish  │
        │   Service   │    S110
        │ Requirements│
        └─────────────┘

┌───────────────────────────────┐
│ For Each Service Type          │
│                         S120   │
│  ┌──────────────────────────┐  │
│  │ For Each Resource        │  │
│  │      Manager             │  │
│  │                  S130    │  │
│  │  ┌─────────────┐         │  │
│  │  │  Establish  │         │  │
│  │  │    Frame    │  S140   │  │
│  │  │ Boundaries  │         │  │
│  │  └─────────────┘         │  │
│  │                          │  │
│  │  ┌─────────────┐         │  │
│  │  │   Divide    │         │  │
│  │  │   Buffers   │         │  │
│  │  │  Based On   │  S150   │  │
│  │  │    Frame    │         │  │
│  │  │ Boundaries  │         │  │
│  │  └─────────────┘         │  │
│  │                          │  │
│  │  ┌─────────────┐         │  │
│  │  │  Configure  │         │  │
│  │  │ Addressing  │         │  │
│  │  │  To Route   │  S160   │  │
│  │  │    Data     │         │  │
│  │  └─────────────┘         │  │
│  └──────────────────────────┘  │
└───────────────────────────────┘

         ( End )          S170
```

Fig. 8

Begin S200

Examine
Service
Configuration S210

X Ports
Of ADSL? S220

Wireless
LAN? S260

VDSL? S300

Establish 250
Microsecond
Frame
Boundaries S230

Use Entire IFFT
Buffer As Inplace
Buffer,
Containing 2048
Complex Points S240

Establish 4
Microsecond
Frame
Boundaries S270

Divide IFFT Buffer
Into Two Inplace
Buffers, Each
Containing 64
Complex Points.
The Remaining
Locations Are
Unused. S280

Establish 250
Microsecond
Frames And
Divide Into 8
Timeslots S310

Divide IFFT Buffer
Into Eight Inplace
Buffers, Each
Containing 256
Complex Points S320

Configure IFFT Butterfly
Addressing To Cycle
Through A Given 256-
Point Inplace Buffer
During Each Timeslot.
The Dual-MACC
Butterfly Engine Is
Allocated To Perform
Two IFFT's In Parallel. S330

Configure IFFT Butterfly
Addressing To Cycle
Through Each 64-Point
Inplace Buffer. The
Dual-MACC Butterfly
Engine Is Allocated To
Perform Two IFFT's In
Parallel. S290

Configure IFFT
Butterfly
Addressing To
Cycle Through
The 2048-Point
Inplace Buffer
During Each
Frame. The
Dual-MACC
Butterfly Engine
Is Fully
Allocated To
The Single
IFFT. S250

End S340

Fig. 9

| |
|---|
| ADSL port 1 512-pt FFT inplace buffer |
| ADSL port 2 512-pt FFT inplace buffer |
| ADSL port 3 512-pt FFT inplace buffer |
| ADSL port 4 512-pt FFT inplace buffer |
| ADSL port 5 512-pt FFT inplace buffer |
| ADSL port 6 512-pt FFT inplace buffer |
| ADSL port 7 512-pt FFT inplace buffer |
| ADSL port 8 512-pt FFT inplace buffer |

768 Multiply-accumulates per pass, addressing local to port 1 FFT buffer

768 Multiply-accumulates per pass, addressing local to port 2 FFT buffer

768 Multiply-accumulates per pass, addressing local to port 3 FFT buffer

768 Multiply-accumulates per pass, addressing local to port 4 FFT buffer

768 Multiply-accumulates per pass, addressing local to port 5 FFT buffer

768 Multiply-accumulates per pass, addressing local to port 6 FFT buffer

768 Multiply-accumulates per pass, addressing local to port 7 FFT buffer

768 Multiply-accumulates per pass, addressing local to port 8 FFT buffer

Fig. 10

VDSL
4096-pt
FFT inplace
buffer

6144 Multiply-
accumulates per pass,
addressing throughout
4096-point FFT buffer

Fig. 11